

Page: 1

Compilation date: 10/01/2011

Revision date: 19/04/2012

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Product code: DYL 18

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Household stain remover. 5 x 30 g.

1.3. Details of the supplier of the safety data sheet

Company name: SPOTLESS PUNCH LIMITED

Betchworth House 57-65 Station Road

Redhill Surrey RH1 1DL UK

Tel: +44 (0)1737 781 300 Fax: +44 (0)1737 769 607

Email: consumer@spotlesspunch.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1737 781 300

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36

Most important adverse effects: Irritating to eyes.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36: Irritating to eyes.

Safety phrases: S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Page: 2

medical advice.

S46: If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM PERCARBONATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
239-707-6	15630-89-4	O: R8; Xn: R22; Xi: R41	Ox. Sol. 2: H272; Acute Tox. 4: H302; Eye Dam. 1: H318; Ox. Sol. 3: H272	25-50%

SODIUM CARBONATE

207-838-8	497-19-8	Xi: R36	Eye Irrit. 2: H319	25-50%
-----------	----------	---------	--------------------	--------

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

270-115-0	68411-30-3	Xi: R38; Xi: R41	-	1-5%	
-----------	------------	------------------	---	------	--

Non-hazardous ingredients:

SUBTILISIN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
232-752-2	9014-01-1	Xi: R37/38; Xi: R41; Sens.: R42; N:	STOT SE 3: H335; Skin Irrit. 2: H315;	<1%
		R50	Eye Dam. 1: H318; Resp. Sens. 1:	
			H334; Aquatic Acute 1: H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Water. Water

spray.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Page: 4

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Hand protection: PVC gloves. Rubber gloves. Gloves (alkali-resistant).

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Powder
Colour: Off-white
Odour: Pleasant

Solubility in water: Soluble

pH: < 11.5 (10% sol)

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Humidity. Heat.

10.5. Incompatible materials

Materials to avoid: Acids. Bases. Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>2000	mg/kg

DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Page: 5

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

DYLON COLOUR CATCHER +OXI STAIN REMOVAL WITH HYGIENE

Page: 6

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Sections 2 & 12: PBT - Persistence Bioaccumulation Toxicity

Phrases used in s.2 and 3: H272: May intensify fire; oxidiser.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

R8: Contact with combustible material may cause fire.

R22: Harmful if swallowed.

R36: Irritating to eyes.

R37/38: Irritating to respiratory system and skin.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R42: May cause sensitisation by inhalation.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.